

# A-WB

Water – Based Primer

## DESCRIPTION

A-WB is a special water-based acrylic primer designed for various substrates.

It improves adhesion between waterproof coatings and substrates, assists moisture prevention, and seals the surface.

## KEY CHARACTERISTICS

- Creep penetration and strong bonding performance.
- Fast drying, consistent with other coatings.

## SUITABLE SUBSTRATES

- Concrete, Blockwork, Cementitious Screeds & Render
- Plasterboard, chipboard that complies with AS/NZS 1859.1
- Compressed flooring,
- PVC (longer dry times apply)
- CSR Hebel, FC Sheeting, Scyon, James Hardie FC Flooring
- Milled finish Aluminium
- Extruded polyurethane foam

## APPLICATION RANGE

- Brush, roller, or spray application. on clean, dry substrates.



- ▶ **Fast drying**
- ▶ **Solvent free**
- ▶ **Great adhesion**
- ▶ **Non-hazardous**

**20 KG / 18 LITRES**

## COVERAGE

- 0.2–0.3 kg/m<sup>2</sup>

## TEMPERATURE & DRYING

- Optimum temp 5–40°C, dry time ≤ 2h at 23°C.

## CLEANING

Clean tools with water immediately after use.

## PERFORMANCE DATA

Physical State	Liquid
Colour	Blue
Packaging	Plastic bucket
Coverage	0.2–0.3 kg/m <sup>2</sup>
Density	≈1.05 g/cm <sup>3</sup>
Dry Time	30mins to 1hr (23°C)

## STORAGE & HANDLING

- Store in cool, dry place above 5°C. Protect from frost.
- Shelf life: 12 months in unopened container.

## SAFETY & ENVIRONMENTAL

- Non-hazardous, solvent-free, low VOC.
- Ensure adequate ventilation during use.
- Wear gloves and eye protection as a precaution.

## COMPLIANCE & NOTES

- Water-based, environmentally responsible formulation.
- Data is typical and subject to variation. Test suitability prior to application.

## CONTACT

### Armourseal Pty Ltd

Unit 36, #36 Turner Road, Smeaton Grange NSW 2567

**Phone:** 0418 261 479 | **Emergency:** 02 9037 2994

**Email:** support@armourseal.net