

# AMOURFLEX-MS

Sealant and Bond Breaker

## DESCRIPTION

A one-component, MS polymer-based sealant designed for use as both a flexible joint sealant and bond breaker.

This sealant provides durable adhesion to most common construction substrates with excellent waterproofing performance.

## FEATURES & BENEFITS

- Excellent adhesion to concrete, masonry, timber, metals, plastics.
- Highly flexible – accommodates movement in joints.
- Weather, UV, and mildew resistant.
- Low VOC, solvent-free, environmentally friendly.
- Paintable after curing.

## APPLICATIONS

- Waterproofing bond breaker for wet areas (bathrooms, balconies, laundries).
- Perimeter sealing of windows and doors.
- Expansion and control joints in concrete and masonry.
- General purpose construction sealant.



## TECHNICAL DATA

Form	Paste / Sausage (600 mL)
Colour	White / Grey
Density	~1.6 g/cm <sup>3</sup>
Application Temperature	+5 °C to +35 °C
Skin Time	~30 minutes (23 °C, 50% RH)
Cure Rate	~3 mm per 24 hrs (23 °C, 50% RH)
Hardness (Shore A)	25–35
Movement Capability	±20%
Shelf Life	10 months (unopened, cool dry)

## COVERAGE

One 600 mL sausage yields approx. 6 linear metres at a 10 × 10 mm joint.

## APPLICATION INSTRUCTIONS

- Substrates must be clean, dry, and free of dust, oil, or contaminants.
- Use backing rod where required.
- Apply sealant in a continuous bead. Tool off within skin time.
- Allow curing before exposure to water.

## PACKAGING & STORAGE

- **Packaging:** 600 mL foil sausages.
- **Storage:** Store unopened in cool, dry conditions, out of direct sunlight.
- **Shelf Life:** 10 months from date of manufacture.

## STANDARDS & COMPLIANCE

- Complies with NCC 2022 requirements for waterproofing.
- Tested to relevant Australian Standards for wet-area applications.

## CONTACT

### Armourseal

Unit 36, #36 Turner Road, Smeaton Grange NSW 2567

**Phone:** 0418 261 479 | **Emergency:** 02 9037 2994

**Email:** support@armourseal.net